



Full-Line Product Summary

Fiber Optic Transport

Live-Link™ Remote Camera Interface System: Designed to handle day-to-day news remote interfacing with ease, Live-Link offers a cost-effective, portable, single-mode optical interface for ENG and OB vans, SNG vehicles, and production trailers. Full support is provided for digital (HD and SD) and analog video, on-air and cue audio, intercom, and Ethernet data. Clear labeling and controls right-where-you-need-them-to-be make the operator learning curve literally minutes. Live-Link is also an ideal infrastructure solution for airports, stadiums, and arenas.



Mobile Broadcast

IFB Plus Model 2 Central Controller: This single rack-space unit contains all the circuitry to implement a sophisticated 2-channel IFB system for electronic news gathering (ENG) and outside broadcast (OB) vans, satellite news gathering (SNG) vehicles, and mobile production facilities. Interruptible foldback (also known as talent cueing) allows reporters and other on-air talent to receive program audio along with audio cues from production personnel, generally directors and producers.



IFB Plus Model 22 and Model 24 Access Stations: Used to access the Model 2's IFB channels, the Model 22 is installed at producer or director locations. Up to four Model 22s can be connected to, and powered by, a Model 2 Central Controller. The Model 24 is installed with two Model 2s to create a 4-channel IFB system, providing producer or director locations with access to IFB channels. Includes five pushbutton switches, one for each IFB channel and "all-call." Up to four Model 24s can be connected to, and powered by, two Model 2 units. Unit are normally installed with a Model 11A Gooseneck Microphone and Model 25A or 27A 19-inch rack adapter.



IFB Plus Model 32A Talent Amplifier: Self-contained amplifier module designed for use by talent or production personnel. A channel selector switch, along with level control, allows either IFB channel to drive a talent earpiece or headset. A combination of up to four Model 32A or Model 33 units can be supported by the Model 2.



IFB Plus Model 33 Talent Amplifier: Advanced, self-contained amplifier module designed for use by production personnel. A channel selector switch, along with two level controls, allows either IFB channel, or a user-adjusted mix of the two IFB channels, to drive a talent earpiece or headset. A combination of up to four Model 32A or Model 33 units can be supported by the Model 2's talent amplifier output.



Model 740 Audio Mixer: Specifically designed for ENG and general audio use, this single-rack-space unit features six mic/line inputs, a monaural audio mix bus, a 10-segment LED level meter, and a monitor section.



Model 742 Audio Mixer: Designed for use in ENG vehicles and various general audio applications, this single rack-space unit features four mic/line inputs, four line inputs, two audio buses, two 10-segment LED level meters, and a monitor section.



Model 750 Audio Mixer: A high-performance audio mixer designed for use in ENG, SNG, and specialized broadcast applications. Features include four mic/line inputs, two stereo line inputs, and two stereo output buses. The unit mounts in two standard rack spaces.



Intercom and IFB

Model 45 2-Wire to 4-Wire Interface: Designed to interface a 2-wire full-duplex party-line intercom circuit with a 4-wire audio circuit associated with a matrix intercom system. Other specialized audio system interfacing applications can also be supported. Applications include television sports and special event broadcasting, theme park and theater installations, corporate events, and industrial testing environments.



Model 46 Dual 2-Wire to 4-Wire Interface: A single rack-space unit that interfaces 2-wire full-duplex party-line intercom circuits with 4-wire audio circuits associated with matrix intercom systems. The unit provides two independent full-featured 2-channel interfaces each with automatic nulling capability. Applications include television sports and special-event broadcasting, theme park and theater installations, corporate events, and industrial testing environments.



Model 41 and Model 42A Line-Level Audio to IFB Circuit Interfaces: Optimized for “broadcast booth” and semi-portable applications, these advanced single rack-space units are specifically designed to link matrix intercom systems with IFB-compatible belt packs and announcer’s consoles. Both units have four independent channels that create industry-standard IFB circuits, each supplying a 30 volt DC power feed and two audio channels. Features include back-panel IFB output connectors, dual LED level meters, and a headphone output to allow sophisticated monitoring of audio and DC signals associated with IFB circuits. In addition, the Model 42A also has front-panel IFB output connectors.



Model 72 Level Meter / Interface: This compact, portable unit “strips” audio from single- and dual-channel intercom and IFB circuits. The unit is used for numerous broadcast and production applications, as well as serving as a troubleshooting and maintenance aid. The Model 72 is powered by an intercom or IFB line.



Model 34 Talent Amplifier: A self-contained amplifier module designed for use with single- or 2-channel IFB systems, the Model 34 features dual level controls, a mono/stereo switch, and both ¼-inch and 3.5 mm output jacks. The unit can be used with Models 41 or 42A Interfaces. These units are fully compatible with industry-standard RTS® 4000-series IFB systems.



Announcer’s Consoles

Model 233 Announcer’s Console: This high-performance unit supports specialized applications such as stadium announcement and live-event production. Available resources include an integrated sidetone section, two line-level audio talkback outputs, two line-level audio inputs, a sophisticated dual-channel intercom interface, and a tally output. The tabletop unit provides great audio performance, numerous user features, and excellent audio performance.



Model 230 Announcer’s Console: This feature-rich unit supports numerous applications, including on-air television and radio broadcasting, stadium announcement, and live-event production. Resources include an IFB input, two line-level audio inputs, a sophisticated dual-channel intercom interface, and a single line-level audio talkback output. The tabletop unit includes extensive configurable parameters and excellent audio performance throughout.



Model 220 Announcer’s Console: An enhanced unit that supports a variety of applications, including on-air television and radio broadcasting. Features include an IFB input, two line-level audio inputs, and two talkback outputs. The tabletop unit includes numerous configurable parameters and resources.



Model 210 Announcer’s Console: An advanced unit suitable for a variety of applications, including on-air television sports broadcasting. Features include an IFB input and single talkback output. Many configurable features are contained in this compact tabletop unit.



Announcer's Consoles, continued

Model 212 Announcer's Console: This digital audio version supports a variety of applications, including on-air television and radio broadcasting, voice-over booths, and stadium announcement. The compact tabletop unit provides excellent audio quality and includes many configurable operating parameters. Features include AES3id (unbalanced coax) digital inputs and outputs, a bidirectional digital interface, and optional AES3 (balanced) digital inputs and outputs.



Model 44 Interface: Designed to work with 200-series announcer's consoles, the unit serves as an interconnection "hub," providing power and signal routing for up to six announcer's consoles. Appropriate for in-studio as well as field broadcast applications. Of special note is its applicability for use in the live television sports industry.



StudioComm Monitoring Systems

5.1 Surround: Digital In/Digital Out

StudioComm 76DB/77B Surround Monitoring System: This all-digital surround monitoring system (Model 76DB Central Controller and Model 77B Control Console) is optimized for broadcast post-production and master control applications. The system allows connection and flexible routing of two surround (5.1) inputs, three stereo inputs, one surround (5.1) output, and one stereo auxiliary output. All inputs are AES3id compatible (unbalanced, 75 ohms); outputs are software-selectable for compatibility with AES3 (balanced, 110 ohms) or AES3id (unbalanced, 75 ohms). Features include Dolby® E metadata dialnorm display and response, and configurable input-to-output delay for synchronizing audio with video displays. One Model 76DB Central Controller supports a combination of up to four Model 77B or Model 71 Control Consoles. (Model 77B Control Console shown.)



StudioComm 76D/77 Surround Monitoring System: An all-digital surround monitoring system (Model 76D Central Controller and Model 77 Control Console) that includes two surround (5.1) inputs, three stereo inputs, one surround (5.1) output, and one stereo output. All inputs are AES3id compatible (unbalanced, 75 ohms); outputs are software-selectable for compatibility with AES3 (balanced, 110 ohms) or AES3id (unbalanced, 75 ohms). Highlights include configurable input-to-output delay for synchronizing audio with video displays. One Model 76D Central Controller supports a combination of up to four Model 77 or Model 71 Control Consoles. (Model 77 Control Console shown.)



5.1 Surround: Digital In/Analog Out

StudioComm 76B/77B Surround Monitoring System: This surround monitoring system (Model 76B Central Controller and Model 77B Control Console) is optimized for broadcast post-production and master control applications. Features include digital input and analog output capability along with Dolby E metadata dialnorm display and response. Allows connection and flexible routing of two surround (5.1) inputs, three stereo inputs, one surround (5.1) output, and one stereo auxiliary output. All inputs are AES3id compatible (unbalanced, BNC connectors); outputs are electronically balanced analog. One Model 76B Central Controller supports a combination of up to four Model 77B or Model 71 Control Consoles. (Model 77B Control Console shown.)



StudioComm 76/77 Surround Monitoring System: A surround monitoring system (Model 76 Central Controller and Model 77 Control Console) with digital input and analog output capability. Features include two surround (5.1) inputs, three stereo inputs, one surround (5.1) output, and one stereo output. All inputs are AES3id compatible (unbalanced, BNC connectors); outputs are electronically balanced analog. One Model 76 Central Controller supports a combination of up to four Model 77 or Model 71 Control Consoles. (Model 77 Control Console shown.)



Compact Control Console

Model 71 Control Console: A compact "command center" for use with a StudioComm 76/77, 76D/77, 76B/77B, or 76DB/77B system. Provides additional user locations with the most frequently desired functions: level adjustment, reference level, and dim Up to three Model 71s can be connected to, and powered by, a central controller.



7.1 Surround: Analog In/Analog Out

StudioComm 78/79 Surround Monitoring System: A 7.1 surround monitoring system (Model 78 Central Controller and Model 79 Control Console) with support for two 7.1 inputs and one 7.1 monitor output. Includes features such as -12 dBV to +6 dBu input levels, extensive downmix capability, and integrated bass management. THX® pm3 approved. (Model 79 Control Console shown.)



StudioComm Monitoring Systems (continued)

5.1 Surround: Analog In/Analog Out

StudioComm 74/75 Surround Monitoring System with Talkback: This system (Model 74 Central Controller and Model 75 Control Console) is designed for advanced 5.1 surround monitoring applications. Features include two 5.1 and two stereo inputs, two 5.1 monitor outputs, and an integrated headphone cue (“talkback”) system. Allows connection of up to four Model 35 Talent Amplifiers. (Model 75 Control Console shown.)



StudioComm 68A/69A Surround Monitoring System: Designed for 5.1 surround monitoring applications, this system (Model 68A Central Controller and Model 69A Control Console) supports two 5.1 and two stereo inputs, and one 5.1 and one stereo monitor output. Includes features such as -12 dBV to +6 dBu input levels, downmix, and mono. (Model 69A Control Console shown.)



Model 65 Bass Manager: An analog processor designed to allow enhanced multi-channel monitoring. While designed to directly connect to the Model 68A Central Controller, the Model 65 is compatible with virtually every monitor system. The single-rack-space unit provides a “5.1” input, five main outputs, and two subwoofer outputs.



Stereo: Analog In/Analog Out

StudioComm 55/56 Stereo Monitoring System with Talkback: This monitoring system (Model 55 Central Controller and Model 56 Control Console) features four stereo inputs, one control room output, a dub (copy) output, and two communications functions. Allows connection of up to four Model 35 Talent Amplifiers. (Model 56 Control Console shown.)



StudioComm 60A/61 Stereo Monitoring System: This basic StudioComm system (Model 60A Central Controller and Model 61 Control Console) features control room monitoring, dub (copy) output, integrated headphone cue system, and auxiliary switcher. (Model 61 Control Console shown.)



Talent Amplifier

Model 35 Talent Amplifier: This portable amplifier module drives one or two pairs of headphones. Connects to StudioComm 55/56 and StudioComm 74/75 systems; up to four Model 35s per system.



Distribution Amplifiers


Model 81 Stereo Analog Audio Distribution Amplifier: An analog distribution amplifier with one stereo input and eight stereo outputs. The inputs use 3-pin XLR-type connectors; two 25-pin D-subminiature connectors are used with the outputs. Features ExactCal input calibration system, balanced inputs and outputs, and sonic excellence.



Model 82 Stereo Analog Audio Distribution Amplifier: An analog distribution amplifier with one stereo input and four stereo outputs. All inputs and outputs use 3-pin XLR-type connectors. Features ExactCal input calibration system, balanced inputs and outputs, and sonic excellence.



Model 85 AES / EBU Digital Audio Distribution Amplifier: A digital distribution amplifier with two AES/EBU digital inputs and eight AES/EBU digital outputs. Allows AES/EBU signals to be distributed to multiple inputs (receivers) without incurring data transmission errors.



In addition to our main product lines, several accessories and cable assemblies are available. These accessories and cable assemblies are designed with the special needs users require. The end results are systems that are flexible, versatile, and extremely space efficient. For detailed information on all Studio Technologies products and accessories visit our website.

E and E Exports, Inc.

Signal Hill, California USA
www.ee-exports.com
Exporters of Studio Technologies products

Studio Technologies, Inc.

We design and manufacture feature-rich broadcast and professional audio products. We're known for building solid, dependable, easy-to-use products developed for the way professionals work. Our products are used worldwide by television and radio stations, sports broadcasters, stadiums and arenas, recording studios, and film and production companies.

© by Studio Technologies, Inc., June 2009 Skokie, Illinois USA www.studio-tech.com